



EMAIL: FILTRATION@JOHNBROOKS.CA

CG55 SERIES LIQUID/GAS COALESCERS

CG55-002-05-15

COST EFFECTIVE COALESCENCE

These elements have been specially engineered to provide the most cost effective high efficiency liquid coalescence of gas streams on the market.

The introduction of proprietary interception, coalescence, and drainage layers pleated in conjunction with a high efficiency micro-fiber media ensures high efficiency separation of sub-micron liquid aerosols from gas streams while minimizing fluid carry-over.

FEATURES AND BENEFITS

- Direct alternative for common conical and cylindrical liquid gas coalescing elements
- Provides high efficiency removal of unwanted liquid contaminants
- Available in both 99.98% and 99.0% efficiency ratings
- High surface area providing low pressure drop
- End caps are designed for easy change-out
- Buna and Viton® O-rings used as standard sealing elastomers (other materials available)

COMMON APPLICATIONS

- Amine plant feed gas and treated gas
- Suction and discharge of compressors
- Fuel Gas purification
- Protection of molecular sieve beds, alumina beds, activated carbon beds, flare systems, glycol units and metering systems
- Turbine Feed Gas

COMMON LIQUID CONTAMINANTS

- Compressor lubrication oils, water, hydrocarbon condensates, amines, glycols, solvents, completion fluids, brine, and other liquid phase contaminates

ELEMENT DIMENSIONS

Outside Diameter: 5.50"

Length: 36"

Cylindrical Shape



PRODUCT SPECIFICATIONS

Gas Micron Ratings: 0.1 & 0.3 Micron
@ both 99.0% and 99.98%

Maximum Operating Conditions:
200°F (93.3°C) Continuous Operating
Temp.

Recommended Clean Pressure Drop:
≤ 2 PSID

Recommended Change-Out Differential
Pressure: 12 PSID

Maximum Recommended
Differential Pressure: 15 PSID

Normal Flow Path: Inside-to-outside

CARTRIDGE CODING

CG55	001	T	G	36	3	V
GAS COALESCER SERIES	GAS MICRON RATING	NON-MEDIA COMPONENTS	MEDIA	LENGTH	END CAP	O-RING
CG55 - Standard CGA55 - (Amine Compatible)	001 - 0.1 Micron (99.98%) 003 - 0.3 Micron (99.98%) 001A - 0.1 Micron (99.0%) 003A - 0.3 Micron (99.0%)	T - Tinned Steel	G - Glass Fiber	36 - 36"	3 - SOE (w-bolt hole)	B - Buna V - Viton®

Notice: The information presented here is based on tests and data which JOHN BROOKS COMPANY believes to be reliable, but their accuracy or completeness is not guaranteed. JOHN BROOKS COMPANY MAKES NO WARRANTIES, EXPRESS OR IMPLIED, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The determination of whether the JOHN BROOKS COMPANY product is fit for a particular purpose or application is the responsibility of the user.



**SPRAYING
PUMPING
FILTERING
AND VALVES**

1-877-624-5757
www.johnbrooks.ca