



EMAIL: FILTRATION@JOHNBROOKS.CA



HPPC Series Filter Cartridges

*Economically Efficient
Pleated Filter Cartridges*

Product Specifications

Media: Polypropylene

Gaskets/O-Rings:

Buna-N, EPDM, Silicone,
Teflon Encapsulated Viton
(O-Rings only), Viton

Polypropylene micron ratings:

0.2, 0.25, 0.45, 0.5, 1.0,
2.0, 5.0, 10, 25, 50 μm

Dimensions

Nominal lengths:

5" 9.75" 10" 20" 30" 40"
12.7 24.8 25.4 50.8 76.2 101.6 cm

Outside diameter: 2.7" (6.86 cm)

Inside diameter: 1.0" (2.54 cm)

Operating Parameters

Maximum operating temperature:

176°F (80°C)

Maximum differential pressure:


75 psid @ 70°F (5.2 bar @ 21°C)
30 psid @ 176°F (2.0 bar @ 80°C)

Maximum reverse pressure:

40 psid @ 70°F (2.8 bar @ 21°C)

Recommended change-out pressure:

35 psid (2.4 bar)



This cost effective, disposable filter element can be used for a wide range of applications. The filter is constructed of pleated polypropylene filter media with high surface area that allows for greater system flow rate.

FEATURES & BENEFITS

- Micron ratings from 0.2 to 50 μm — Broad application range
- Fixed pore structures — Resists unloading of captured contaminant
- Polypropylene Construction — Inert to many process fluids
- Various Gasket/O-Ring materials — Compatible with a variety of fluids
- Economically efficient filtration
- Manufactured in continuous lengths up to 40 inches

CERTIFICATIONS

- USP Class VI: Meets USP Class VI Biological Test for Plastics
- FDA Listed Materials: All materials comply with FDA Title 21 of the Code of Federal Regulations Sections 174.5, and 177.1520, as applicable for food and beverage contact.
- European Directive for Direct Food Contact: European Regulation No. 1935/2004 and European Regulation 10/2011: Tested for migration behavior and is suitable for contact with all kinds of foodstuffs with minimal rinse-up. Data available upon request.


HPPC NOMENCLATURE INFORMATION

Filter Type	Retention Rating (microns)		Nominal Length (inches)		End Configuration		Gasket or O-Ring	
HPPC Series	0.2	2	-5	-20	P	Double Open End	B	Buna-N
	0.25	5	-9.75*	-30	P2	226/Flat Single Open End	E	EPDM
	0.45	10	-10	-40	P3	222/Flat Single Open End	S	Silicone
	0.5	25			P7	226/Fin Single Open End	T	Teflon encap. Viton (O-Rings only)
	1	50			P8	222/Fin Single Open End	T	Teflon Gasket
Example: HPPC 2-20P8V					AM	Single Open End, Internal O-Ring	T	Teflon Gasket
					NPC	Double Open End, Internal O-Ring	V	Viton
HPPC	2		-20		P8		V	

*Available only for DOE (P) configuration

HPPC FLOW RATE

Typical Flow Rate Clean Water at Ambient Temperature
(per 10" cartridge)



For liquids other than water, multiply pressure drop by the fluid viscosity in centipoise

The micron ratings shown at various efficiency and beta ratio value levels were determined through laboratory testing, and can be used as a guide for selecting cartridges and estimating their performance. Under actual field conditions, results may vary somewhat from the values shown due to the variability of filtration parameters.

Testing was conducted using the single-pass test method, water at 3 gpm/10" cartridge. Contaminants included latex beads, coarse and fine test dust. Removal efficiencies were determined using dual laser source particle counters.

REMOVAL EFFICIENCY

Beta Ratio Efficiency	Beta 50 98%	Beta 10 90%
0.2 µm	0.28	0.20
0.25 µm	0.35	0.25
0.45 µm	0.6	0.45
0.5 µm	0.7	0.5
1 µm	1.5	1.0
2 µm	2.7	2.0
5 µm	7.0	5.0
10 µm	12.0	10.0
25 µm	32.0	25.0
50 µm	70.0	50.0

$$\text{Beta Ratio} = \frac{\text{Upstream particle counts}}{\text{Downstream particle counts}}$$



HPPC-0119

1-877-624-5757
www.johnbrooks.ca