



EMAIL: FILTRATION@JOHNBROOKS.CA



HPPG Series Filter Cartridges

Glass Fiber Cartridges

Product Specifications

Media: Borosilicate Microfiberglass with Acrylic Binder

Inner Core: Polypropylene

Support Layers: Polyester

Cage, End Caps: Polypropylene

Gaskets/O-Rings:

Buna-N, EPDM, Silicone,
Teflon Encapsulated Viton
(O-Rings only), Viton

Micron rating:

0.2, 0.45, 1.0*, 3.0, 10, 30 μm

*1 micron grade features all FDA listed materials of construction

Dimensions

Nominal lengths:

5" 9.75" 10" 20" 30" 40"
12.7 24.8 25.4 50.8 76.2 101.6 cm

Outside diameter: 2.55" (6.48 cm)

Inside diameter: 1.0" (2.54 cm)

Operating Parameters

Maximum operating temperature: 176°F (80°C)

Maximum differential pressure:

50 psid @ 70°F (3.4 bar @ 21°C)
25 psid @ 176°F (1.7 bar @ 80°C)

Maximum reverse pressure:

15 psid @ 70°F (2.8 bar @ 21°C)

Recommended

change-out pressure:

35 psid (2.4 bar)

This high efficiency, economical filter element is constructed of pleated Borosilicate Microfiberglass media that combines excellent flow rates with exceptional service life to support a wide range of chemical and industrial applications. The nominally-rated borosilicate microfiber depth matrix has a natural positive charge that aids in the retention of negatively charged particulates such as colloidal materials or contaminants that may form haze within a fluid. The depth characteristic of glass media also provides enhanced retention of deformable particles as compared to typical polypropylene media. In addition, the slightly smaller diameter ensures easy retrofit in installed housings designed to accept depth filters.

FEATURES & BENEFITS

- Micron ratings from 0.2 to 30 μm — Broad application range
- Uniform pore size — High removal efficiency
- Long service life — Minimizes maintenance costs
- Fixed pore construction — Eliminates dirt unloading at maximum differential pressure
- Manufactured in continuous lengths up to 40 inches

TYPICAL APPLICATIONS

- Chemicals
- Blowdown post filter
- Inks
- Oil & Gas
- Cutting oils
- Paints
- Coatings


HPPG NOMENCLATURE INFORMATION

Filter Type	Retention Rating (microns)		Nominal Length (inches)		End Configuration		Gasket or O-Ring
HPPG Series	0.2	3	-5	-20	P	Double Open End	B Buna-N
	0.45	10	-9.75*	-30	P2	226/Flat Single Open End	E EPDM
	1	30	-10	-40	P3	222/Flat Single Open End	S Silicone
					P7	226/Fin Single Open End	T Teflon encap. Viton (O-Rings only)
				P8	222/Fin Single Open End	V Viton	
Example: HPPG 3-10P7B							
HPPG	3		-10		P7		B

*Available only for DOE (P) configuration

HPPG FLOW RATE

Typical Flow Rate Clean Water at Ambient Temperature
(per 10" cartridge)



For liquids other than water, multiply pressure drop by the fluid viscosity in centipoise

REMOVAL EFFICIENCY

Beta Ratio Efficiency	Beta 10	Beta 20	Beta 100	Beta 1000	Beta 5000
0.2 µm	90%	95%	99%	99.9%	99.98%
0.45 µm	0.2	0.3	0.6	0.8	1.0
1 µm	0.45	0.6	0.8	1.8	2.0
3 µm	1.0	1.3	2.0	3.5	4.0
10 µm	3.0	4.0	5.5	9.0	10.0
30 µm	10.0	12.0	15.0	17.0	18.0
	30.0	35.0	38.0	42.0	45.0

$$\text{Beta Ratio} = \frac{\text{Upstream particle counts}}{\text{Downstream particle counts}}$$

The micron ratings shown at various efficiency and beta ratio value levels were determined through laboratory testing, and can be used as a guide for selecting cartridges and estimating their performance. Under actual field conditions, results may vary somewhat from the values shown due to the variability of filtration parameters.

Testing was conducted using the single-pass test method, water at 2.5 gpm/10" cartridge. Contaminants included latex beads, coarse and fine test dust. Removal efficiencies were determined using dual laser source particle counters.



HPPG-0619

1-877-624-5757
www.johnbrooks.ca