



EMAIL: FILTRATION@JOHNBROOKS.CA

MAXIMUM CAPACITY 650 SERIES PLEATED BAG FILTERS

MC650-002-05-15

COST EFFECTIVE FILTRATION

HART introduces its next generation of Pleated Bag filters, the 650 Maximum Capacity style bag.

The original HART Platinum 650 style bag has been re-engineered to provide a greater range of micron ratings and more dirt holding capacity.

These next generation pleated bags are constructed with polypropylene components and are available in a wide variety of filter media.

BENEFITS

- Highest dirt holding capacity of all bag filter series
- Highly researched pleat design maximizes dirt holding capacity and surface area
- Wide-range of media options allows for compatibility with many fluids
- Broad range of micron ratings and efficiencies
- Simple installation into existing equipment without equipment modification
- Absolute rated media with fixed pore structure prevents particle unloading and provides reliable results in critical applications

COMMON APPLICATIONS

- Water and Wastewater, Process Fluids, Acids, Bases, Amines, Glycols, Brines, Machine Coolants

DIMENSIONS

Outside Diameter: 6.25"
Inside Diameter: 2.00"
Length: 20" and 26"

MATERIALS OF CONSTRUCTION

Filter Media: Polypropylene, Micro-fiberglass, Nylon and Polyester
Center Core: Polypropylene
Netting: Polypropylene or Nylon
End Caps: Polypropylene



PRODUCT SPECIFICATIONS

Micron Ratings @ 99.98% (beta 5000):
0.5, 2, 5, 10, 20, 30, 40, 50, 70, 100
and 135 micron

Maximum Operating Conditions:
185°F (85°C) continuous operating
temperature

Recommended Flow Rate for
Optimal Dirt Loading:
25 GPM for 20" filter
35 GPM for 26" filter

Maximum Recommended Flow Rate:
100 GPM for 20" filter
125 GPM for 26" filter

Recommended Differential Pressure for
change-out: 25 PSID

MEDIA MICRON RATING AT EFFICIENCY

FILTER MODEL	65D	65E	65F	65G	65H	65J	65K	65L	65M	65N
99.00% (beta 100)	0.3	1	2	5	10	15	25	40	70	100
99.98% (beta 5000)	0.5	2	5	10	20	30	40	70	100	135

DIRT HOLDING CAPACITY (LBS)* Per 26" filter element

FILTER MODEL	65D	65E	65F	65G	65H	65J	65K	65L	65M	65N
Pounds of Solids (20")	7.1	8.1	8.7	8.8	9.0	9.0	9.2	9.2	9.6	9.6
Pounds of Solids (26")	9.2	10.5	11.3	11.4	11.7	11.7	12.0	12.0	12.5	12.5

CLEAN PRESSURE DROP (PSID)* Per 26" filter element

FILTER MODEL	65D	65E	65F	65G	65H	65J	65K	65L	65M	65N
PSID @ 15 GPM	0.34	0.26	0.22	0.20	0.18	0.16	0.15	0.14	0.13	0.10
PSID @ 25 GPM	0.58	0.47	0.41	0.40	0.37	0.36	0.35	0.32	0.30	0.25
PSID @ 50 GPM	1.18	0.99	0.87	0.85	0.83	0.81	0.79	0.77	0.73	0.64

CARTRIDGE CODING

MC	65E	P	P	20	1	E
MAX CAPACITY SERIES	MICRON RATING @ 99.98%	NON-MEDIA COMPONENTS	MEDIA	LENGTH	HOUSING	O-RING
	65D - 0.5 Micron 65E - 2 Micron 65F - 5 Micron 65G - 10 Micron 65H - 20 Micron 65J - 30 Micron 65K - 40 Micron 65L - 70 Micron 65M - 100 Micron 65N - 135 Micron	*P - Polypropylene	*P - Polypropylene G - Glass N - Nylon R - Polyester	20 - 20" 26 - 26"	1 - Rosedale 2 - FSI 5 - Over-the-top style G - Plenty	B - Buna-N E - EPDM V - Viton® U - Santoprene™
					Contact JBCL For Additional Cap Options	

* The raw polypropylene materials composing these filters are FDA compliant according to CFR Title 21.

Notice: The information presented here is based on tests and data which JOHN BROOKS COMPANY believes to be reliable, but their accuracy or completeness is not guaranteed. JOHN BROOKS COMPANY MAKES NO WARRANTIES, EXPRESS OR IMPLIED, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The determination of whether the JOHN BROOKS COMPANY product is fit for a particular purpose or application is the responsibility of the user.



**SPRAYING
PUMPING
FILTERING
AND VALVES**

1-877-624-5757
www.johnbrooks.ca