

BIMETAL THERMOMETER 3 AND 5 in 304 STAINLESS STEEL (CONTINUED)
CENTER BACK FIXED STEM
MODELS B3 AND B5

To order, use the code in the corresponding column

Range	MODEL B3 3 in (76 mm) Ø fixed stem length (center back connection 1/2 in nptm)				
	2 1/2 in (63 mm)	4 in (100 mm)	6 in (150 mm)	9 in (225 mm)	12 in (300 mm)
-40 to 160°F / -40 to 70°C	B325-01	B340-01	B360-01	B390-01	
30 to 240°F / 0 to 115°C	B325-03	B340-03	B360-03	B390-03	
50 to 300°F / 10 to 150°C	B325-05	B340-05	B360-05	B390-05	
50 to 500°F / 10 to 260°C	B325-07	B340-07	B360-07	B390-07	
0 to 250°F / -20 to 120°C	B325-09	B340-09	B360-09	B390-09	B3120-09
200 to 1,000°F / 90 to 540°C	B325-11	B340-11	B360-11	B390-11	B3120-11
25 to 125°F / -5 to 50°C	B325-12				

Range	MODEL B5 5 in (127 mm) Ø fixed stem length (center back connection 1/2 in nptm)				
	2 1/2 in (63 mm)	4 in (100 mm)	6 in (150 mm)	9 in (225 mm)	12 in (300 mm)
-40 to 160°F / -40 to 70°C	B525-01	B540-01	B560-01	B590-01	
30 to 240°F / 0 to 115°C	B525-03	B540-03	B560-03	B590-03	
50 to 300°F / 10 to 150°C	B525-05	B540-05	B560-05	B590-05	
50 to 500°F / 10 to 260°C	B525-07	B540-07	B560-07	B590-07	
0 to 250°F / -20 to 120°C	B525-09	B540-09	B560-09	B590-09	
200 to 1,000°F / 90 to 540°C	B525-11	B540-11	B560-11	B590-11	B5120-11

Option

Other ranges and stem lengths are available upon request.